



# Recycled Item 4

## Material Safety Data Sheet

Peckham Industries, Inc.  
20 Haarlem Ave.  
White Plains, NY 10603

Revision Date: 8/14/2006

### Emergency Overview

**Appearance:** Brown, gray, solid mixture

**Odor:** Faint odor

#### WARNING:

When hardened product is subjected to mechanical forces which generate dust particles, exposure to respirable silica-containing dust is possible. Repeated overexposures to very high levels of respirable crystalline silica (quartz, cristobalite, tridymite) for periods as short as six months have caused acute silicosis. Acute silicosis is a rapidly progressive, incurable lung disease that is typically fatal. Symptoms include (but are not limited to): shortness of breath, cough, fever, weight loss, and chest pain.

### Hazard Rankings

	HMIS	NFPA
Health Hazard	0	0
Fire Hazard	0	0
Flammability	0	0
Reactivity	0	0

### Protective Equipment

Minimum Recommended  
See Section 8 for Details

This recommendation reflects  
minimum PPE.



## SECTION 1. PRODUCT IDENTIFICATION

**Trade Name:** Recycled Item 4      **Technical Contact:** (914) 949-2000  
**Medical Emergency:** (800) 424-9300

**CAS Number:** Mixture      **CHEMTREC Emergency:** (800) 424-9300  
**(United States Only)**

**Synonyms:** Recycled Hardened Concrete, Recycled Crushed Stone, Recycled Hot Mix Asphalt, Recycled Brick

## SECTION 2. COMPOSITION

---

Component Name(s)	CAS Registry No.	Concentration (%)
Aggregate (limestone, granite, hot mix asphalt, brick, concrete, soil, etc.)	Mixture	60-95
- Composition varies naturally; typically contains quartz (crystalline silica)	14808-60-7	> 1
Hydrated Portland Cement	65997-15-1	3-40

## SECTION 3. HAZARDS IDENTIFICATION

---

**Major Route(s) of Entry:** Inhalation.

### Signs and Symptoms of Acute Exposure

- Eye Contact:** Direct contact with dust may cause irritation by mechanical abrasion.
- Skin Contact:** Direct contact may cause irritation by mechanical abrasion. Not expected to be a significant exposure route following short-term exposure.
- Inhalation:** Dusts may irritate the nose, throat, and respiratory tract by mechanical abrasion. Coughing, sneezing, and shortness of breath may occur following exposures in excess of appropriate exposure limits.
- Ingestion:** Not for consumption. However, if ingested, the material may become slightly caustic and cause tissue irritation. Ingestion of large amounts may cause gastrointestinal irritation and blockage.

### Medical Conditions Aggravated By Exposure:

Inhaling dust may aggravate existing respiratory disease(s) and/or dysfunctions.  
Exposure to dust may aggravate existing skin and/or eye conditions.

## SECTION 4. FIRST AID MEASURES

---

**Take proper precautions to ensure your own health and safety before attempting rescue or providing first aid.**

- Eye Contact:** Immediately flush eye(s) with clean water for at least 15 minutes, while holding the eyelid(s) open. Occasionally lift the eye(s) to ensure thorough rinsing. Beyond flushing, do not attempt to remove material from the eye(s). Contact a physician if irritation persists or later develops.
- Skin Contact:** Wash with soap and water. Contact a physician if irritation persists or later develops.
- Inhalation:** Remove to fresh air. Dust in throat and nasal passages should clear spontaneously. Contact a physician if irritation persists or later develops.

**Ingestion:** If person is conscious, give large quantity of water and induce vomiting; however, never attempt to make an unconscious person drink or vomit. Get immediate medical attention.

## SECTION 5. FIRE FIGHTING MEASURES

---

<b>Flash Point</b>	Not applicable	<b>Flammable Limits in Air</b>	Not applicable
<b>Hazardous Combustion Products</b>	Not applicable	<b>Unusual Fire and Explosion Hazards</b>	None known
<b>Extinguishing Media</b>	None required		

## SECTION 6. ACCIDENTAL RELEASE MEASURES

---

**Protective Measures** Not applicable

**Spill Management** Do not dry sweep spilled material. Spilled material, where dust can be generated, may overexpose personnel to respirable crystalline silica-containing dust. Wetting of spilled material and/or use of respiratory protective equipment may be necessary. Do not dry sweep spilled material.

## SECTION 7. HANDLING AND STORAGE

---

Follow personal protection and controls set forth in Section 8 of this MSDS when handling this product.

**Handling** Respirable crystalline silica-containing dust may be generated during crushing, processing, handling, and storage when product is subjected to mechanical forces.

**Storage** Do not store near food and beverages or smoking materials.

## SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

---

**Personal Protective Equipment** Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to OSHA regulations. The following pictograms represent the minimum requirements for personal protective equipment. For certain operations, additional PPE may be required.



<b>Eye Protection</b>	Safety glasses with side shields should be worn as minimum protection. Dust goggles should be worn when excessively (visible) dusty conditions are present.
<b>Skin Protection</b>	See "Hygiene" section below.
<b>Respiratory</b>	Activities that generate excess dust from product require the use of NIOSH approved dust respirators where dust levels exceed or are likely to exceed appropriate exposure limits. For respirable quartz levels that exceed or are likely to exceed an 8hr-TWA of 0.1 mg/m <sup>3</sup> , a NIOSH approved dust respirator must be worn. For respirable quartz levels that exceed or are likely to exceed an 8hr-TWA of 0.5 mg/m <sup>3</sup> , a NIOSH approved HEPA filter respirator must be worn. If respirable quartz levels exceed or are likely to exceed an 8hr-TWA of 5 mg/m <sup>3</sup> , a NIOSH approved positive pressure, full face respirator or equivalent is required. Respirator use must comply with applicable MSHA or OSHA standards, which include provisions for a user training program, respirator repair and cleaning, respirator fit testing, and other requirements.
<b>Ventilation</b>	Activities that generate dust in confined areas may require the use of local exhaust or general ventilation adequate to maintain exposures below appropriate exposure limits.
<b>Hygiene</b>	Wash dust-exposed skin with soap and water before eating, drinking, smoking, and using toilet facilities. Wash work clothes after each use.
<b>Other Control Measures</b>	Ample clean water should always be readily available for skin and emergency eye washing. Respirable dust and quartz levels should be monitored during activities that generate dust. Dust and quartz levels in excess of appropriate exposure limits should be reduced by all feasible engineering controls, including (but not limited to) wet suppression, ventilation, process enclosure, and enclosed employee work stations.

### Occupational Exposure Guidelines

When exposure to this product and other chemicals in concurrent, the exposure limit must be defined in the workplace.

**Limestone (Calcium Carbonate):** TLV = 10 mg/m<sup>3</sup>; OSHA PEL = 15 mg/m<sup>3</sup> (total dust), OSHA PEL = 5 mg/m<sup>3</sup> (respirable fraction)

**Other Particulates:** TLV = 10 mg/m<sup>3</sup> (inhalable/total particulate, not otherwise classified), TLV = 3 mg/m<sup>3</sup> (respirable particulate, not otherwise classified); OSHA PEL = 15 mg/m<sup>3</sup> (total particulate, not otherwise regulated), OSHA PEL = 5 mg/m<sup>3</sup> (respirable particulate, not otherwise regulated)

**Respirable Crystalline Silica (quartz):** TLV = 0.05 mg/m<sup>3</sup>; MSHA and OSHA PEL = 10 mg/m<sup>3</sup> ÷ (% SiO<sub>2</sub> + 2); MSHA-Proposed and OSHA Proposed PEL = 0.1 mg/m<sup>3</sup>

**Respirable Dust:** MSHA and OSHA PEL = 10 mg/m<sup>3</sup> ÷ (%SiO<sub>2</sub> + 2)

**Total Dust:** MSHA PEL =  $30 \text{ mg/m}^3 \div (\% \text{SiO}_2 + 3)$ ; OSHA PEL =  $30 \text{ mg/m}^3 \div (\% \text{SiO}_2 + 2)$

ACGIH and OSHA have determined that adverse effects are not likely to occur in the workplace provided exposure levels do not exceed the appropriate TLVs/PELs. However, because of the wide variation in individual susceptibility; lower exposure limits may be appropriate for some individuals including persons with pre-existing medical conditions.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

---

**Attention:** The data below are typical values and do not constitute a specification.

<b>Color:</b> Gray, brown	<b>Physical State:</b> Solid	<b>Odor:</b> Faint odor
<b>pH:</b> NA	<b>Vapor Pressure:</b> NA	<b>Vapor Density (Air = 1):</b> NA
<b>Boiling Point:</b> NDA	<b>Solubility:</b> Negligible	<b>Melting Point:</b> NA
<b>Specific Gravity:</b> 1.7-3.0	<b>% Volatile, By Volume (@ 100°F):</b> 0%	

## SECTION 10. STABILITY AND REACTIVITY

---

<b>Chemical Stability</b>	Stable
<b>Incompatibility With Other Materials</b>	Contact with powerful oxidizing agents such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride may cause fire and/or explosions. Silica dissolves readily in hydrofluoric acid producing a corrosive gas-silicon tetrafluoride.
<b>Hazardous Decomposition Products</b>	None
<b>Hazardous Polymerization</b>	Not known to occur.
<b>Conditions to Avoid:</b>	Avoid contact with incompatible materials (see above).

## SECTION 11. TOXICOLOGICAL INFORMATION

---

### CHRONIC TOXICITY

When hardened product is subjected to mechanical forces which generate dust particles, exposure to respirable silica-containing dust is possible. Prolonged and repeated inhalation of respirable crystalline silica-containing dust in excess of appropriate exposure limits has caused silicosis, a lung disease. Not all individuals with silicosis will exhibit symptoms (signs) of the disease. However, silicosis can be progressive, and symptoms can appear at any time, even years after exposure has ceased. Symptoms of silicosis may include, but are not limited to, the following: shortness of breath; difficulty breathing with or without exertion; coughing; diminished work capacity; diminished chest expansion; reduction of lung volume; right heart enlargement and/or failure. Smoking may increase the risk of developing lung disorders, including emphysema and lung cancer. Persons with silicosis have an increased risk of pulmonary tuberculosis infection.

Respirable dust containing newly broken silica particles has been shown to be more hazardous to animals in laboratory tests than respirable dust containing older silica particles of similar size. Respirable silica particles which had aged for sixty days or more showed less lung injury in animals than equal exposures of respirable dust containing newly broken particles of silica.

There are reports in the literature suggesting that excessive crystalline silica exposure may be associated with adverse health effects involving the kidney, scleroderma (thickening of the skin caused by swelling and thickening of fibrous tissue) and other autoimmune disorders. However, this evidence has been obtained primarily from case reports involving individuals working in high exposure situations or those who have already developed silicosis; and therefore, this evidence does not conclusively prove a causal relationship between silica or silicosis and these adverse health effects. Several studies of persons with silicosis also indicate an increased risk of developing lung cancer, a risk that increases with the duration of exposure. Many of these studies of silicotics do not account for lung cancer confounders, especially smoking.

Recycled Item 4 is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). In October 1996, an IARC Working Group re-assessing crystalline silica, a component of this product, designated respirable crystalline silica as carcinogenic (Group 1). The NTP's Report on Carcinogens, 9th edition, lists respirable crystalline silica as a "known human carcinogen." In year 2000, the American Conference of Governmental Industrial Hygienists (ACGIH) listed respirable crystalline silica (quartz) as a suspected human carcinogen (A-2). These classifications are based on sufficient evidence of carcinogenicity in certain experimental animals and on selected epidemiological studies of workers exposed to crystalline silica.

## **SECTION 12. ECOLOGICAL INFORMATION**

---

### **ECOTOXICITY**

No specific data on this product. This material is not expected to be harmful to aquatic organisms.

### **ENVIRONMENTAL FATE**

No specific data on this product.

## **SECTION 13. DISPOSAL CONSIDERATIONS**

---

Recycled Item 4 can be disposed of as common waste. Dispose of waste materials in accordance with applicable federal, state, and local laws and regulations.

## **SECTION 14. TRANSPORT INFORMATION**

---

**The shipping description below may not represent requirements for all modes of transportation, shipping methods or locations outside the United States.**

**DOT Shipping Name:** Label according to the OSHA Hazard Communication standard [29 CFR 1910.1200 (f)] and applicable state and local laws and regulations.

**DOT Hazard Class:** None

**DOT Identification Number:** Not applicable

**Placard:** None required

**DOT Packing Group:** Not applicable

**Emergency Response Guide No.:** Not applicable

## **SECTION 15. REGULATORY INFORMATION**

---

### **CHEMICAL INVENTORIES:**

All of the components of this material are on the Toxic Substances Control Act (TSCA) Chemical Inventory or are exempt.

## **SECTION 16. ADDITIONAL INFORMATION**

---

### **Scale For NFPA and HMIS Ratings:**

0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme, PPE:-Personal Protective Equipment Index Recommendation, \*-Chronic Effect Indicator. These values are obtained using the guidelines or published evaluations prepared by the National Fire Protections Association (NFPA) or the National Paint and Coating Association (for HMIS ratings).

### **ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:**

TLV - Threshold Limit Value  
STEL - Short-term Exposure Limit  
NA - Not Applicable  
NDA - No Data Available

TWA - Time Weighted Average  
REL/PEL - Recommended/Permissible Exposure Limit  
CAS - Chemical Abstract Service Number  
NE - Not Established

**THE INFORMATION IN THIS MSDS WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESSED OR IMPLIED REGARDING ITS CORRECTNESS. SOME INFORMATION PRESENTED AND CONCLUSIONS DRAWN HEREIN ARE FROM SOURCES OTHER THAN DIRECT TEST DATA ON THE SUBSTANCE ITSELF. THIS MSDS WAS PREPARED AND IS TO BE USED ONLY FOR THIS PRODUCT. IF THE PRODUCT IS USED AS A COMPONENT IN ANOTHER PRODUCT, THIS MSDS INFORMATION MAY NOT BE APPLICABLE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION OR PRODUCTS FOR THEIR PARTICULAR PURPOSE.**

**THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE, AND DISPOSAL OR THE PRODUCT ARE BEYOND OUR CONTROL AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE, OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.**